

SIROMER MK RANGE

Compact Chassis, High Power.



SIROMER MK LOADER

Self levelling loaders engineered for Siromer's MK Range.

Fitted with Euro brackets and 4in1 bucket.

MODEL B871

Lift Capacity 750kg

Max Lift Height 2350mm

Dump Height 1730mm

Digging Depth 140mm

Bucket Width 1400mm

Bucket Capacity 0.43m cu

Weight 540kg

SIROMER 404MK

The Siromer 40hp MK is available with a fully airconditioned cab.

Complete with shuttle synchro transmission with 8 forward and 8 reverse speeds.

The main shift allows you to shift "on the fly" making operation smooth.

Engineered for power this tractor comes as standard with electric stop start and front mudguards.

MODEL

404MK CAB (K40, K4C)

Horsepower

40HP

Maximum 3pl Lift

1200kg

Weight

1415kg (1705kg cab)

Size (Length x Width x Height)

3480mm x 1560mm x 2560mm (2460mm cab)

Wheel Base

1810mm

Turning Circle

2700mm

Ground Clearance

353mm

PTO Speed

2 Speed (540, 1000RPM)

Clutch

10 Inch Dual Stage Clutch

Wheel Drive

Selectable 4WD

Engine

4 Cylinder, 4 Stroke, Water Cooled Direct Injection Diesel

Fuel Tank Capacity

32 liters

Brakes

Disc Brakes

Rated Speed

2400rpm

Cultivation Depth Control

Position Control

Gearbox

Synchro Shuttle: 8 Forward, 8 Reverse.

Min/Max Speed

1 mph / 18 mph

Steering

Hydraulic Power Steering

Hydraulic Type

Dual Double Acting Spool combined single acting spool (20L/min)

Hitching Mechanism

Three Point Linkage (CAT I)

Hitch Device

Clevis Drawbar

Electrics

12V 100AH, Combined Instrument Panel, Aux Trailer Connection

Tyres

Ag: 7.5-16 Front, 12.4-24 Rear

Radial: 260/70R16 Front, 320/85R24 Rear (extra £800)

Industrial: 15-19.5 Front, 28*9-15 Rear (extra £1200)

Turf: 9.5-16 Front, 13-20 Rear (extra £800)